

Race time / Lap: _____

Best lap: _____

Name: _____
Date: _____
Track: _____

Diff. Oil

Rear: _____

Diff. Type

- ☐ Gear Diff
☐ Ball Diff

Track Conditions

- Size: ☐ Open ☐ Med. ☐ Tight
Traction: ☐ High ☐ Med. ☐ Low ☐ Wet
Surface: ☐ Smooth ☐ Med. ☐ Bumpy

Tire

Front _____ Rear _____
Type: _____ Type: _____
Foam: _____ Foam: _____

Electric System

ESC Type: _____
Motor Type: _____
Motor Gear/Spur Gear: _____
Battery Type: _____

Front Suspension

1 2 3
mm
Camber: _____ mm (°)
Upper () mm
Lower () mm
1 2 3 1 2
Toe Angle: _____ mm (°) 0 2.5 2.5 5 -5

Front Lower Arm Holder
☐ 25° ☐ 30°
☐ Standard ☐ 25g Brass

Front Sway bar ☐ Use _____ mm
☐ None

Diff. Position
Ride High: _____ mm

Oil: _____
Spacer: _____ mm
Pistons: _____
Spring: _____

Rear Suspension

1 2 3 4 5
mm
Camber: _____ mm (°)
4.7mm
5.7mm
6.7mm
7.7mm
1 2 3 1 2 3
Rear Toe-In
F
R
0.5 1.0
0.5 1.0

Wing Angle ☐ 0 ☐ +3 ☐ -3
Notes: _____

Wing Position
Body: _____
Rear Wing: _____
Front Wing: _____

Rear Sway bar ☐ Use _____ mm
☐ None


Ride High: _____ mm

Oil: _____
Spacer: _____ mm
Pistons: _____
Spring: _____

Option Parts List


Front lower arm

☐ Carbon composite Hard Material ☐ Standard Material



Rear lower arm

☐ Carbon composite Hard Material ☐ Standard Material



Side guard

☐ Carbon composite Hard Material ☐ Standard Material

